

**LODE  KING**

[www.lodeking.com](http://www.lodeking.com)



**AHV SUPER-B**

ALUMINUM GRAIN TRAILER

# SPECIFICATIONS

## BODY STRUCTURE

- LENGTH** ..... Lead 28'6", Pull 30'5"
- EXTERIOR WIDTH** 102"
- INTERIOR WIDTH** 97.75"
- HEIGHT** ..... 82" and 84" wall height available
- STRUCTURE** ..... Steel king pin section and suspension frame; walls of double skin aluminum with internal stiffeners, riveted construction
- SLOPES** ..... Aluminum, 30 deg. except 43 deg. at rear of Lead
- HOPPERS** ..... Aluminum, formed with two rows of stiffeners, chute frame riveted to hopper cone
- LADDERS** ..... Aluminum, front and rear with interior access steps
- LANDING GEAR** .. Contender 51000, 2 speed with attached handle
- MUDFLAPS** ..... Heavy duty, black rubber, anti-sail
- TARP** ..... Michel's with flip-stops, reinforcement over roof-bows, fiberglass ridge-pole
- TARP SUPPORTS**.. Aluminum roof bows and end caps
- LIGHTING** ..... 7-Way connector at front, Truck-lite LED lights and wiring harness
- FINISH** ..... Pre-painted aluminum exterior, natural aluminum hoppers and interior surfaces, painted steel king pin section and suspension frame

## RUNNING GEAR

- SUSPENSION** .... Intraax AANT23K air ride
- AXLES** ..... Hendrickson 5.75" round, 77.5" track
- ABS** ..... Meritor Wabco
- OIL SEALS** ..... Guardian HP
- HUBS** ..... 10 stud, hub piloted, cast or lighter weight options
- DRUMS** ..... Outboard, cast or lighter weight options
- BRAKES** ..... 16 1/2" x 7" quick change
- BRAKE LININGS**.. Abex 931-162
- WHEELS** ..... 22.5" or 24.5" steel or aluminum
- TIRES** ..... Wide range of Michelin and Bridgestone products available

## OPTIONS

- 4 in a row full coverage 102" wide mudflaps ahead of landing gear
- Brake pot belting ahead of suspension
- Load gauge enclosure with internal light and a sealed window in the door
- Air outlet in load gauge enclosure
- Implement style loading light for each hopper
- Implement style unloading light
- Chute openings from both sides
- Tow hooks at rear of pull
- Placard holders
- Hubodometer
- Lift Axles
- Extended service brake linings
- Closure plates at front and rear
- Vent in each hopper
- Round stainless steel fenders
- Flat aluminum fenders

## TRAILER VOLUME (CUBIC FT.)

Wall Height	Lead 28'6"		Pull 30'5"		Total	
	WATER LEVEL	HEAPED	WATER LEVEL	HEAPED	WATER LEVEL	HEAPED
82"	1239	1335	1428	1531	2667	2866
84"	1275	1371	1466	1570	2741	2941



## LODE-KING INDUSTRIES

A Division of Triple E Canada Ltd.

Box 1146, 135 Canada Street  
 Winkler, MB Canada R6W 4B2  
 T (204) 325-4345 F (204) 325-5369  
 www.lodeking.com



Product improvement is an ongoing process a Lode-King Industries. Thus we reserve the right to change any specifications or components on any specifications or components on any or all products without prior notice; errors or omissions excepted. Lode-King Industries is under no obligation to undertake modifications to units manufactured prior to changes in specifications. Printed in Canada.

**Distributed By:**