

LODE  KING

www.lodeking.com



 **Prestige**

HGF TANDEM AXLE

PRESTIGE GRAIN TRAILER

SPECIFICATIONS

BODY STRUCTURE

- LENGTH** 36', 40'
WIDTH 102"
WALL HEIGHT.... 74" (option 77")
KING PIN 24" (option 18")
WALLS Corrugated 16 gauge steel side walls, 14 gauge at high stress areas, front and rear end walls aluminum
- TOWER**
- STRUCTURE**..... Tubular frames with formed channel buttress
SLOPES..... Aluminum, 30 deg. front and rear
HOPPERS..... 14 gauge steel, overlapped corners, two rows of stiffeners all around, full height steel divider wall between hoppers
HOPPER DOORS.. 16" x 24" with chain and sprocket drive, removable crank and multiple position locking mechanism
LADDERS..... Aluminum, front and rear with interior access steps
LANDING GEAR.. Holland Mark V, 2 speed with attached handle
FENDERS..... Smooth aluminum fenders at front and at rear
MUDFLAPS..... Heavy duty, black rubber, anti-sail at rear and ahead of second hopper
TARP..... Michel's or with open and closed handle lock positions
TARP SUPPORTS.. Aluminum end caps and aluminum roof bows
LIGHTING..... 7 way connector at front, sealed lights, Lode-King sealed wiring system
FINISH..... Units are washed, shotblasted, zinc undercoated on exterior, primed, and finished in Dupont Imron paint

RUNNING GEAR

- SUSPENSION** Intraax AANT23K air ride
AXLES..... Hendrickson 5.75" round on Intraax. All axles 77.5" track
ABS..... Meritor Wabco
OIL SEALS..... Guardian HP
HUBS..... 10 stud, hub pilot mount, cast or lighter weight options
DRUMS..... Outboard, cast or lighter weight options
BRAKES..... 16 1/2" x 7" quick change
BRAKE LININGS.. Abex 931-162
WHEELS..... Steel disc painted white or powder coated silver or aluminum
TIRES..... Wide range of Bridgestone and Michelin products available

OPTIONS

- 4 in a row full coverage 102" wide mudflaps ahead of landing gear
- 3 in a row mudflaps ahead of second hopper
- Brake pot belting ahead of suspension
- Load gauge enclosure with internal light and a sealed window in the door
- Air outlet in load gauge enclosure
- LED lights
- Implement style loading light for each hopper
- Implement style unloading light
- Chute openings from both sides
- Sidewall vent in each hopper
- Aluminum fill plate in bumper with Lode-King logo
- Tow hooks at rear
- Placard holders
- Hubodometer
- Vibrator brackets
- Lift axles
- Extended service brake linings

TRAILER VOLUME (CUBIC FT.)

Wall Height	36' Length		40' Length	
	WATER LEVEL	HEAPED	WATER LEVEL	HEAPED
74"	1570	1680	1730	1800
77"	1645	1755	1810	1942



LODE-KING

A Division of Triple E Canada Ltd.

Box 1146, 135 Canada Street
 Winkler, MB Canada R6W 4B2
 T (204) 325-4345 F (204) 325-5369
 www.lodeking.com



Product improvement is an ongoing process a Lode-King Industries. Thus we reserve the right to change any specifications or components on any specifications or components on any or all products without prior notice; errors or omissions excepted. Lode-King Industries is under no obligation to undertake modifications to units manufactured prior to changes in specifications. **Printed in Canada.**

Distributed By: