

**LODE  KING**

[www.lodeking.com](http://www.lodeking.com)



  
**Prestige**

**HGF TRIPLE AXLE**

PRESTIGE GRAIN TRAILER

# SPECIFICATIONS

## BODY STRUCTURE

- LENGTH** . . . . . 45'
- WIDTH** . . . . . 102"
- WALL HEIGHT** . . . 80" (option 84")
- KING PIN** . . . . . 15"
- WALLS** . . . . . Corrugated 16 gauge steel side walls, 14 gauge at high stress areas
- TOWER**
- STRUCTURE** . . . . Tubular frames with formed channel buttress
- SLOPES** . . . . . Aluminum, 33 deg. front and 30 deg. rear
- HOPPERS** . . . . . 14 gauge steel, overlapped corners, two rows of stiffeners all around, full height steel divider wall between hoppers
- HOPPER DOORS** . . 16" x 24" with chain and sprocket drive, removable crank and multiple position locking mechanism
- LADDER** . . . . . Aluminum, front and rear with interior access steps
- LANDING GEAR** . . Holland Mark V, 2 speed with attached handle
- FENDERS** . . . . . Front and rear smooth aluminum fenders
- MUDFLAPS** . . . . Heavy duty, black rubber, anti-sail at rear and ahead of second hopper
- TARP** . . . . . Michel's with open and closed handle lock positions
- TARP SUPPORTS** . Aluminum end caps and aluminum roof bows
- LIGHTING** . . . . . 7 way connector at front, sealed lights, Lode-King sealed wiring system
- FINISH** . . . . . Units are washed, shotblasted, zinc undercoated on exterior, primed, and finished in Dupont Imron paint

## RUNNING GEAR

- SUSPENSION** . . . . Intraax AANT23K air ride
- AXLES** . . . . . Hendrickson 5.75" round on Intraax. All axles 77.5" track
- ABS** . . . . . Meritor Wabco
- OIL SEALS** . . . . . Guardian HP
- HUBS** . . . . . 10 stud, hub pilot mount, cast or lighter weight options
- DRUMS** . . . . . Outboard, cast or lighter weight options
- BRAKES** . . . . . 16½" x 7" quick change
- BRAKE LININGS** . . Abex 931-162
- WHEELS** . . . . . Steel disc painted white or powder coated silver or aluminum
- TIRES** . . . . . Wide range of Bridgestone and Michelin products available

## OPTIONS

- 4 in a row full coverage 102" mudflaps ahead of landing gear
- 3 in a row mudflaps ahead of second hopper
- Brake pot belting ahead of suspension
- Load gauge enclosure with internal light and a sealed window in the door
- Air coupling in load gauge enclosure
- LED lights
- Implement style loading light for each hopper
- Implement style unloading light
- Chute opening from both sides
- Sidewall vent in each hopper
- Aluminum fill plate in bumper with Lode-King logo
- Tow hooks at rear
- Placard holders
- Hubodometer
- Vibrator brackets
- Lift Axles
- Extended service brake linings

## TRAILER VOLUME (CUBIC FT.)

Wall Height	Front Hopper		Rear Hopper		Total	
	WATER LEVEL	HEAPED	WATER LEVEL	HEAPED	WATER LEVEL	HEAPED
80"	870	940	910	990	1780	1930
84"	922	994	971	1046	1893	2040



## LODE-KING

A Division of Triple E Canada Ltd.

Box 1146, 135 Canada Street  
 Winkler, MB Canada R6W 4B2  
 T (204) 325-4345 F (204) 325-5369  
 www.lodeking.com



Product improvement is an ongoing process at Lode-King Industries. Thus we reserve the right to change any specifications or components on any or all products without prior notice; errors or omissions excepted. Lode-King Industries is under no obligation to undertake modifications to units manufactured prior to changes in specifications. Printed in Canada.

**Distributed By:**